

## Process for the production of high temperature-resistant insulation layers for cables and wires

**Publication number:** DE3233504 (A1)

**Publication date:** 1984-03-15

**Inventor(s):** GROEPPEL DIETER [DE]; SIEMSEN GISELA [DE]

**Applicant(s):** SIEMENS AG [DE]

**Classification:**


**- international:** *H01B3/04; H01B3/08; H01B3/46; H01B7/29; H01B13/16; H01B3/02; H01B3/46; H01B7/17; H01B13/06; (IPC1-7): H01B7/28*

**- European:** H01B3/04; H01B3/08B; H01B3/46; H01B7/29; H01B13/16


**Application number:** DE19823233504 19820909


**Priority number(s):** DE19823233504 19820909


**Also published as:**


 DE3233504 (C2)

**Cited documents:**

 DE1007593 (C)

 DE3233517 (A1)

 DE3007341 (A1)

 DE2629540 (A1)

### Abstract of **DE 3233504 (A1)**

The invention relates to a process for the production of insulation layers based on glass and mica for cables and wires and has the object of designing a process of this type in particular so that a continuous procedure is possible, even for the production of high temperature-resistant layers. The invention proposes that glass and mica powders are sintered together, that the powdered sintered product is electrophoretically deposited on the metallic conductor and subsequently sintered, and that a layer of mica and silicone rubber is applied electrophoretically to the glass/mica layer and subsequently cured.

---

Data supplied from the **esp@cenet** database — Worldwide